



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁷ :

B01J 2/04, A61K 9/16

A1

(11) International Publication Number:

WO 00/37169

(43) International Publication Date:

29 June 2000 (29.06.00)

(21) International Application Number: PCT/GB99/04355

(22) International Filing Date: 21 December 1999 (21.12.99)

(30) Priority Data:

9828204.9

21 December 1998 (21.12.98)

GB

(71) Applicant (for all designated States except US): SMITHKLINE BEECHAM PLC [GB/GB]; New Horizons Court, Brentford, Middlesex TW8 9EP (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): MERRIFIED, David, Roy [GB/GB]; SmithKline Beecham Pharmaceuticals, Clarendon Road, Worthing, West Sussex BN14 8QH (GB). VALDER, Christopher, Edmund [GB/GB]; New Frontiers Science Park South, Third Avenue, Harlow, Essex CM19 5AW (GB).


(74) Agent: WALKER, Ralph, Francis; SmithKline Beecham, Corporate Intellectual Property, Two New Horizons Court, Brentford, Middlesex TW8 9EP (GB).

(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: PROCESS AND APPARATUS FOR PRODUCING PARTICLES USING A SUPERCRITICAL FLUID



(57) Abstract

A process, and a suitable apparatus, for production of particles of a material in which a stream of a dispersion of the material in a solvent and a stream of a compressible fluid antisolvent substance are mixed under conditions such that the substance is in compressible fluid antisolvent state. The mixture then flows along a conduit (17) toward an orifice (18), from which it flows into a downstream region in which the compressible fluid antisolvent substance decompresses and the material is isolated in a particulate state. Preferably the antisolvent substance is a supercritical fluid. The process and apparatus can generate a co-formulation of the material with additives which can be introduced in a suitable aqueous or solvent based carrier vehicle.